RANKEM

RFCL LIMITED QUALITY ASSURANCE DEPARTMENT

RESTRICTED CIRCULATION FOR AUTHORISED USE ONLY

MATERIAL SAFETY DATA SHEET

CHEMICAL NAME	NITRIC ACID
CAS No.: [7697-37-2]	Version: 0

Page: 1 of 7

1. General Information

Catalogue Numbers:

RANKEM: N0060, N0070, N0080, N0090, N0066; N0092, N0072, N0067E, N0075

Company Address:

RFCL Ltd. A-3, Okhla Industrial Area Phase – I, Okhla New Delhi – 110020

Company Phone Number:

91-11-42395700

2. Composition Ingredients

Ingredient	CAS No	Percent	Hazardous	
Nitric Acid	7697-37-2	50 - 70%	Yes	
Water	7732-18-5	30 - 50%	No	

3. Hazards Identification

Emergency Overview

POISON! DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. CORROSIVE. LIQUID AND MIST CAUSE SEVERE BURNS TO ALL BODY TISSUE. MAY BE FATAL IF SWALLOWED OR INHALED. INHALATION MAY CAUSE LUNG AND TOOTH DAMAGE.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 4 - Extreme (Poison) Flammability Rating: 0 - None

Reactivity Rating: 3 - Severe (Oxidizer) Contact Rating: 4 - Extreme (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER

GLOVES

Page: 2 of 7

RANKEM

MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

Storage Color Code: White (Corrosive)

Potential Health Effects

Nitric acid is extremely hazardous; it is corrosive, reactive, an oxidizer, and a poison.

Inhalation:

Corrosive! Inhalation of vapors can cause breathing difficulties and lead to pneumonia and pulmonary edema, which may be fatal. Other symptoms may include coughing, choking, and irritation of the nose, throat, and respiratory tract.

Ingestion:

Corrosive! Swallowing nitric acid can cause immediate pain and burns of the mouth, throat, esophagus and gastrointestinal tract.

Skin Contact:

Corrosive! Can cause redness, pain, and severe skin burns. Concentrated solutions cause deep ulcers and stain skin a yellow or yellow-brown color.

Eve Contact:

Corrosive! Vapors are irritating and may cause damage to the eyes. Contact may cause severe burns and permanent eye damage.

Chronic Exposure:

Long-term exposure to concentrated vapors may cause erosion of teeth and lung damage. Long-term exposures seldom occur due to the corrosive properties of the acid.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders, eye disease, or cardiopulmonary diseases may be more susceptible to the effects of this substance.

4. First Aid Measures

Immediate first aid treatment reduces the health effects of this substance.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

DO NOT INDUCE VOMITING! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Page: 3 of 7

RANKEM

MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

5. Fire Fighting Measures

Fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Can react with metals to release flammable hydrogen gas.

Explosion:

Reacts explosively with combustible organic or readily oxidizable materials such as: alcohols, turpentine, charcoal, organic refuse, metal powder, hydrogen sulfide, etc. Reacts with most metals to release hydrogen gas which can form explosive mixtures with air.

Fire Extinguishing Media:

Water spray may be used to keep fire exposed containers cool. Do not get water inside container.

Special Information:

Increases the flammability of combustible, organic and readily oxidizable materials. In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Neutralize with alkaline material (soda ash, lime), then absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Protect from physical damage. Keep out of direct sunlight and away from heat, water, and incompatible materials. Do not wash out container and use it for other purposes. When diluting, the acid should always be added slowly to water and in small amounts. Never use hot water and never add water to the acid. Water added to acid can cause uncontrolled boiling and splashing. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls, Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

2 ppm (TWA), 4 ppm (STEL)

-ACGIH Threshold Limit Value (TLV):

2 ppm (TWA); 4 ppm (STEL)

Page: 4 of 7

RANKEM

MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation*, *A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, wear a supplied air, full-facepiece respirator, airlined hood, or full-facepiece self-contained breathing apparatus. Nitric acid is an oxidizer and should not come in contact with cartridges and canisters that contain oxidizable materials, such as activated charcoal. Canister-type respirators using sorbents are ineffective.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eve Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance : Colorless to yellowish liquid.

Odor : Suffocating, acrid. Solubility : Infinitely soluble.

Specific Gravity : 1.41

pH : 1.0 (0.1M solution)

% Volatiles by volume @ 21C :

(70F) 100 (as water and acid)

Boiling Point : 122C (252F) Melting Point : -42C (-44F)

Vapor Density (Air=1) : 2-3

Vapor Pressure (mm Hg) : 48 @ 20C (68F) Evaporation Rate (BuAc=1) : No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Containers may burst when heated.

Hazardous Decomposition Products:

When heated to decomposition, emits toxic nitrogen oxides fumes and hydrogen nitrate. Will react with water or steam to produce heat and toxic and corrosive fumes.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

A dangerously powerful oxidizing agent, concentrated nitric acid is incompatible with most substances, especially strong bases, metallic powders, carbides, hydrogen sulfide, turpentine, and combustible organics.

Page : 5 of 7

RANKEM

MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

Conditions to Avoid:

Light and heat.

11. Toxicological Information

Nitric acid: Inhalation rat LC50: 244 ppm (NO2)/30M; Investigated as a mutagen, reproductive effector. Oral (human) LDLo: 430 mg/kg.

-----\Cancer Lists\-----

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Nitric Acid (7697-37-2)	No	No	None
Water (7732-18-5)	No	No	None

12. Ecological Information

Environmental Fate:No information found. **Environmental Toxicity:**

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: NITRIC ACID

Hazard Class: 8 UN/NA: UN2031 Packing Group: II

Information reported for product/size: 6.5GL

International (Water, I.M.O.)

Proper Shipping Name: NITRIC ACID

Hazard Class: 8, 5.1 UN/NA: UN2031

Page : 6 of 7

RANKEM

MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

Packing Group: II

Information reported for product/size: 6.5GL

International (Air, I.C.A.O.)

Proper Shipping Name: NITRIC ACID

Hazard Class: 8 UN/NA: UN2031 Packing Group: II

Information reported for product/size:

15. Regulatory Information

\Chemical Inventory Status - Part 1\								
Ingredient	TSCA	EC	Japan 	Australia				
Nitric Acid (7697-37-2)	Yes	Yes	Yes	Yes				
Water (7732-18-5)	Yes	Yes	Yes	Yes				
\Chemical Inventory Status - Part 2\-								
Canad Ingredient	Korea	DSL	NDSL	Phil.				
Nitric Acid (7697-37-2)	Yes	Yes	No	Yes				
Water (7732-18-5)	Yes	Yes	No	Yes				
\Federal, State & International Regulations - Part 1\								
Ingredient	RQ	TPQ	List	Chemical Catg.				
Nitric Acid (7697-37-2)	1000	1000	Yes	No				
Water (7732-18-5)	No	No	No	No				
\Federal, State & International Regulations - Part 2\								
Ingredient	CERCLA	261.33	8(d)					
Nitric Acid (7697-37-2)	1000	No	No					
Water (7732-18-5)	No	No	No					

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No

Reactivity: No (Mixture / Liquid)

Page: 7 of 7

RANKEM MATERIAL SAFETY DATA SHEET

PRODUCT: NITRIC ACID

Australian Hazchem Code: 2PE

Poison Schedule: S6

16. Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.
